

P G PRODUCTS LIMITED

FIREGUARD SOLAS

Instructions for Use and Maintenance

1.0 General

Fireguard comprises the following items

- Helmet assembly with visor and neck curtain
- Jacket
- Trousers
- Mittens
- Wellington Boots

2.0 Donning Trousers

- 2.1 Ensure braces adjustment is fully extended and fold braces down either side of the trousers exposing waist fully.
- 2.2 Remove footwear and place feet into trouser legs.
- 2.3 Pull waistband up to waist.
- 2.4 Insert arms into braces, placing straps over each shoulder without twists. Pull down adjuster straps until comfortable.

3.0 Donning Boots

- 3.1 Pull trouser legs up to knees.
- 3.2 Don boots.
- 3.3 Pull legs down over boots to ankle level.
- 3.4 Adjust tabs at ankles.

4.0 Donning Jacket

- 4.1 Open touch and close and zip at front of jacket opening.
- 4.2 Place arms in sleeves.
- 4.3 Zip up jacket and close flap over ensuring Velcro lines up. Ensure jacket overlaps outside and over the trousers without any rucks.
- 4.4 Close collar using Velcro provided ensuring that it stands up and is not folded down into jacket.
- 4.5 Pull elasticated cuffs down to wrists.

5.0 Donning Helmet

- 5.1 Ensure neck curtain is not folded into helmet and don helmet. Adjust helmet to fit.
- 5.2 Place chinstrap under chin and adjust for comfort and fit.
- 5.3 Visor assembly can be raised and lowered.

Note: Visor must always be in lowered position when fire fighting.

6.0 Donning Gloves

- 6.1 Pull on mittens ensuring sleeve is tucked inside glove

Fireguard is manufactured in specially processed cotton to make it fire retardant and water repellent. The suit can withstand a minimum of 50 wash cycles without loss of performance.

The suit can be machine-washed at temperatures up to 50° C.

After washing it is recommended that the suits be ironed with a warm iron to “reset” the water repellent finish and improve appearance.

USE WASH PROGRAMME 4, MAXIMUM TEMPERATURE 50° C
DO NOT BLEACH
DO NOT DRY CLEAN
WARM IRON

Storage

Store in a cool, dry, well ventilated area away from sunlight. If used with salt water, ensure that salt water is washed off with fresh water and dried before storage otherwise damage may occur to the aluminium surface.