

# P G PRODUCTS LIMITED

## FLAMEGUARD Mk 3 SOLAS

### Instructions for Use and Maintenance

#### 1.0 General

Flameguard Mk 3 SOLAS comprises the following items  
Helmet assembly with visor and neck curtain  
Jacket  
Trousers  
Mittens  
Wellington Boots

#### 2.0 Donning Trousers

- 2.1 Ensure braces adjustment is fully extended and fold braces down either side of the trousers exposing waist fully.
- 2.2 Remove footwear and place feet into trouser legs.
- 2.3 Pull waistband up to waist.
- 2.4 Insert arms into braces, placing straps over each shoulder without twists. Pull down adjuster straps until comfortable.

#### 3.0 Donning Boots

- 3.1 Pull trouser legs up to knees.
- 3.2 Don boots.
- 3.3 Pull legs down over boots to ankle level.

#### 4.0 Donning Jacket

- 4.1 Open Velcro at front of jacket opening.
- 4.2 Place arms in sleeves.
- 4.3 Close flap over ensuring Velcro lines up. Ensure jacket overlaps outside and over the trousers without any rucks.
- 4.4 Close collar using Velcro provided ensuring that it stands up and is not folded down into jacket.
- 4.5 Pull elasticated cuffs down to wrists.

#### 5.0 Donning Helmet

- 5.1 Ensure neck curtain is not folded into helmet and don helmet. Adjust helmet to fit.
- 5.2 Place chinstrap under chin and adjust for comfort and fit.
- 5.3 Visor assembly can be raised and lowered.

**Note: Visor must always be in lowered position when fire fighting.**

#### 6.0 Donning Gloves

- 6.1 Pull on mittens ensuring sleeve is tucked inside glove..

#### Cleaning

Flameguard Mk 3 is constructed from aluminised fabric, which cannot be machine laundered in the normal way.

The outer surface has a wipe clean film surface and cleaning must be limited to the following,

Remove soiling by sponging down with warm water. For severe soiling a mild detergent may be used.

**Maximum drying temperature 50°C.**

**DO NOT DRY CLEAN**

**DO NOT MACHINE WASH**

**DO NOT TUMBLE DRY**

**DO NOT BLEACH**

#### Storage

Store in a cool, dry, well ventilated area away from sunlight. If used with salt water, ensure that salt water is washed off with fresh water and dried before storage otherwise damage may occur to the aluminium surface.